

Cisco Aironet 1140 Series Access Point



Taking Business Mobility Mainstream


The Cisco® Aironet® 1140 Series Access Point is a business-ready, [802.11n access point](#) designed for simple deployment and energy efficiency. The high-performance platform, which offers at least six times the throughput of existing 802.11a/g networks, prepares the business for the next wave of mobile devices and applications. Building on the Cisco Aironet heritage of RF excellence, the 1140 Series combines the industry's most widely deployed 802.11n technology with a sleek industrial design that blends seamlessly into any enterprise environment. Designed for sustainability, the 1140 Series delivers high performance from standard 802.3af Power over Ethernet while decreasing waste with multiunit eco-packs and Energy Star certified power supplies.

RF Excellence

Building on the Cisco Aironet heritage of RF excellence, the 1140 Series delivers industry-leading performance for secure and reliable [wireless](#) connections. Enterprise-class silicon and optimized radios deliver a robust [mobility](#) experience using Cisco M-Drive technology, which includes:

- [ClientLink](#) improves reliability and coverage for legacy clients.
- [BandSelect](#) improves 5-GHz client connections in mixed client environments.
- [VideoStream](#) uses multicast to improve rich-media applications.

All of these features ensure the best possible end-user experience on the wireless network.


<p>Performance with Investment Protection</p> <ul style="list-style-type: none"> • Six times faster than 802.11a/g networks • Backward-compatible with 802.11a/b/g clients • M-Drive technology optimizes RF
<p>Easy Installation and Power Efficient</p> <ul style="list-style-type: none"> • 802.11n performance with existing PoE switches • Sleek design blends into a variety of indoor environments
<p>Secure Interoperability</p> <ul style="list-style-type: none"> • 802.11n compliant • Intel Connect with Centrino Certified
<p>Simplified Network Management</p> <ul style="list-style-type: none"> • Controller-based or standalone deployment options
<p>Secure Connections</p> <ul style="list-style-type: none"> • Supports rogue access point detection and denial of service attacks • Management frame protection detects malicious users and alerts network administrators
<p>Greater Network Capacity</p> <ul style="list-style-type: none"> • Dynamic frequency selection 2 (DFS-2) compliant
<p>Easy-to-Install, Multipurpose Mounting Bracket</p> <ul style="list-style-type: none"> • Designed for easy replacement of existing access points • UL 2043 plenum rated for above ceiling installation options or suspended from drop ceilings. • Locks for theft protection

The Cisco Aironet 1140 Series is a component of the Cisco Unified Wireless Network, which can scale up to 18,000 [access points](#) with full Layer 3 mobility across central or remote locations on the enterprise campus, in branch offices, and at remote sites. The Cisco Unified Wireless Network is the industry's most flexible, resilient, and scalable architecture, delivering secure access to mobility services and applications and offering the lowest total cost of ownership and investment protection by integrating seamlessly with the existing wired network.

Product Specifications

Table 1 lists the product specifications for Cisco Aironet 1140 Series Access Points.

Table 1. Product Specifications for Cisco Aironet 1140 Series Access Points

Item	Specification																																																											
Part Numbers	<p>Cisco Aironet 1140 Series Access Point</p> <ul style="list-style-type: none"> • AIR-LAP1142N-x-K9—Dual-band Controller-based 802.11a/g/n • AIR-LAP1141N-x-K9—Single-band Controller-based 802.11g/n • AIR-AP1142N-x-K9—Dual-band Standalone 802.11a/g/n • AIR-AP1141N-x-K9—Single-band Standalone 802.11g/n • AIR-LAP1142-xK9-PR—Eco-pack (dual-band 802.11a/g/n) 10 quantity Controller-based access points • AIR-AP1142-xK9-5PR—Eco-pack (dual-band 802.11a/g/n) 5 quantity Standalone access points <p>Regulatory domains: (x = regulatory domain)</p> <p>Customers are responsible for verifying approval for use in their individual countries. To verify approval and to identify the regulatory domain that corresponds to a particular country, please visit http://www.cisco.com/go/aironet/compliance.</p> <p>Not all regulatory domains have been approved. As they are approved, the part numbers will be available on the Global Price List.</p>																																																											
Software	<ul style="list-style-type: none"> • Cisco Unified Wireless Network Software Release 7.0 or later. • Cisco IOS® Software Release 12.4(21a)JA 																																																											
Draft 802.11n Version 2.0 (and Related) Capabilities	<ul style="list-style-type: none"> • 2x3 multiple-input multiple-output (MIMO) with two spatial streams • Maximal ratio combining (MRC) • Legacy beamforming (hardware supports this capability; not yet enabled in software) • 20- and 40-MHz channels • PHY data rates up to 300 Mbps • Packet aggregation: A-MPDU (Tx/Rx), A-MSDU (Tx/Rx) • 802.11 dynamic frequency selection (DFS) (Bin 5) • Cyclic shift diversity (CSD) support 																																																											
Data Rates Supported	<p>802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps</p> <p>802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps</p> <p>802.11n data rates (2.4 GHz and 5 GHz):</p> <table border="1"> <thead> <tr> <th rowspan="2">MCS Index¹</th> <th colspan="2">GI² = 800ns</th> <th colspan="2">GI = 400ns</th> </tr> <tr> <th>20-MHz Rate (Mbps)</th> <th>40-MHz Rate (Mbps)</th> <th>20-MHz Rate (Mbps)</th> <th>40-MHz Rate (Mbps)</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>6.5</td> <td>13.5</td> <td>7.2</td> <td>15</td> </tr> <tr> <td>1</td> <td>13</td> <td>27</td> <td>14.4</td> <td>30</td> </tr> <tr> <td>2</td> <td>19.5</td> <td>40.5</td> <td>21.7</td> <td>45</td> </tr> <tr> <td>3</td> <td>26</td> <td>54</td> <td>28.9</td> <td>60</td> </tr> <tr> <td>4</td> <td>39</td> <td>81</td> <td>43.3</td> <td>90</td> </tr> <tr> <td>5</td> <td>52</td> <td>108</td> <td>57.8</td> <td>120</td> </tr> <tr> <td>6</td> <td>58.5</td> <td>121.5</td> <td>65</td> <td>135</td> </tr> <tr> <td>7</td> <td>65</td> <td>135</td> <td>72.2</td> <td>150</td> </tr> <tr> <td>8</td> <td>13</td> <td>27</td> <td>14.4</td> <td>30</td> </tr> <tr> <td>9</td> <td>26</td> <td>54</td> <td>28.9</td> <td>60</td> </tr> </tbody> </table>	MCS Index ¹	GI ² = 800ns		GI = 400ns		20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	0	6.5	13.5	7.2	15	1	13	27	14.4	30	2	19.5	40.5	21.7	45	3	26	54	28.9	60	4	39	81	43.3	90	5	52	108	57.8	120	6	58.5	121.5	65	135	7	65	135	72.2	150	8	13	27	14.4	30	9	26	54	28.9	60
MCS Index ¹	GI ² = 800ns		GI = 400ns																																																									
	20-MHz Rate (Mbps)	40-MHz Rate (Mbps)	20-MHz Rate (Mbps)	40-MHz Rate (Mbps)																																																								
0	6.5	13.5	7.2	15																																																								
1	13	27	14.4	30																																																								
2	19.5	40.5	21.7	45																																																								
3	26	54	28.9	60																																																								
4	39	81	43.3	90																																																								
5	52	108	57.8	120																																																								
6	58.5	121.5	65	135																																																								
7	65	135	72.2	150																																																								
8	13	27	14.4	30																																																								
9	26	54	28.9	60																																																								

¹ MCS Index: The **M**odulation and **C**oding **S**cheme (MCS) index determines the number of spatial streams, the modulation, the coding rate, and data rate values.

² GI: A **G**uard **I**nterval (**GI**) between symbols helps receivers overcome the effects of multipath delays.

Item	Specification				
	10	39	81	43.3	90
	11	52	108	57.8	120
	12	78	162	86.7	180
	13	104	216	115.6	240
	14	117	243	130	270
	15	130	270	144.4	300
Frequency Band and 20-MHz Operating Channels	A (A Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.462 GHz; 11 channels 5.180 to 5.320 GHz; 8 channels 5.500 to 5.700 GHz, 8 channels (excludes 5.600 to 5.640 GHz) 5.745 to 5.825 GHz; 5 channels C (C Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.472 GHz; 13 channels 5.745 to 5.825 GHz; 5 channels E (E Reg Domain): 2.412 to 2.472 GHz; 13 channels <ul style="list-style-type: none"> 5.180 to 5.320 GHz; 8 channels 5.500 to 5.700 GHz, 11 channels I (I Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.472 GHz; 13 channels 5.180 to 5.320 GHz; 8 channels K (K Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.472 GHz; 13 channels 5.180 to 5.320 GHz; 8 channels 5.500 to 5.620 GHz, 7 channels 5.745 to 5.805 GHz, 4 channels 		N (N Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.462 GHz; 11 channels 5.180 to 5.320 GHz; 8 channels 5.745 to 5.825 GHz; 5 channels P (P Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.472 GHz; 13 channels 5.180 to 5.320 GHz; 8 channels S (S Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.472 GHz; 13 channels 5.180 to 5.320 GHz; 8 channels 5.745 to 5.825 GHz; 5 channels T (T Regulatory Domain): <ul style="list-style-type: none"> 2.412 to 2.462 GHz; 11 channels 5.280 to 5.320 GHz; 3 channels 5.500 to 5.700 GHz, 11 channels 5.745 to 5.825 GHz; 5 channels 		
Note: This varies by regulatory domain. Refer to the product documentation for specific details for each regulatory domain.					
Maximum Number of Non-Overlapping Channels	2.4 GHz <ul style="list-style-type: none"> 802.11b/g: <ul style="list-style-type: none"> 20 MHz: 3 802.11n: <ul style="list-style-type: none"> 20 MHz: 3 40 MHz: 1 		5 GHz <ul style="list-style-type: none"> 802.11a: <ul style="list-style-type: none"> 20 MHz: 21 802.11n: <ul style="list-style-type: none"> 20 MHz: 21 40 MHz: 9 		
Note: This varies by regulatory domain. Refer to the product documentation for specific details for each regulatory domain.					
Receive Sensitivity	802.11b -91 dBm @ 1 Mb/s -91 dBm @ 2 Mb/s -91 dBm @ 5.5 Mb/s -88 dBm @ 11 Mb/s	802.11g -86 dBm @ 6 Mb/s -86 dBm @ 9 Mb/s -86 dBm @ 12 Mb/s -86 dBm @ 18 Mb/s -85 dBm @ 24 Mb/s -83 dBm @ 36 Mb/s -78 dBm @ 48 Mb/s -77 dBm @ 54 Mb/s	802.11a -90 dBm @ 6 Mb/s -90 dBm @ 9 Mb/s -90 dBm @ 12 Mb/s -90 dBm @ 18 Mb/s -88 dBm @ 24 Mb/s -85 dBm @ 36 Mb/s -80 dBm @ 48 Mb/s -79 dBm @ 54 Mb/s		
	2.4-GHz 802.11n (HT20) -88 dBm @ MCS0 -87 dBm @ MCS1 -86 dBm @ MCS2 -83 dBm @ MCS3 -80 dBm @ MCS4 -76 dBm @ MCS5 -74 dBm @ MCS6 -73 dBm @ MCS7 -87 dBm @ MCS8 -85 dBm @ MCS9	2.4-GHz 802.11n (HT40) -85 dBm @ MCS0 -85 dBm @ MCS1 -83 dBm @ MCS2 -80 dBm @ MCS3 -77 dBm @ MCS4 -72 dBm @ MCS5 -71 dBm @ MCS6 -70 dBm @ MCS7 -85 dBm @ MCS8 -82 dBm @ MCS9	5-GHz 802.11n (HT20) -91 dBm @ MCS0 -91 dBm @ MCS1 -90 dBm @ MCS2 -87 dBm @ MCS3 -84 dBm @ MCS4 -79 dBm @ MCS5 -77 dBm @ MCS6 -76 dBm @ MCS7 -90 dBm @ MCS8 -89 dBm @ MCS9	5-GHz 802.11n (HT40) -78 dBm @ MCS0 -78 dBm @ MCS1 -78 dBm @ MCS2 -78 dBm @ MCS3 -78 dBm @ MCS4 -75 dBm @ MCS5 -73 dBm @ MCS6 -72 dBm @ MCS7 -76 dBm @ MCS8 -76 dBm @ MCS9	

Item	Specification			
	-83 dBm @ MCS10 -80 dBm @ MCS11 -77 dBm @ MCS12 -73 dBm @ MCS13 -71 dBm @ MCS14 -70 dBm @ MCS15	-80 dBm @ MCS10 -76 dBm @ MCS11 -73 dBm @ MCS12 -69 dBm @ MCS13 -67 dBm @ MCS14 -66 dBm @ MCS15	-86 dBm @ MCS10 -83 dBm @ MCS11 -80 dBm @ MCS12 -75 dBm @ MCS13 -74 dBm @ MCS14 -72 dBm @ MCS15	-76 dBm @ MCS10 -76 dBm @ MCS11 -76 dBm @ MCS12 -71 dBm @ MCS13 -69 dBm @ MCS14 -68 dBm @ MCS15
Maximum Transmit Power	2.4GHz <ul style="list-style-type: none"> • 802.11b <ul style="list-style-type: none"> ◦ 20 dBm with 1 antenna • 802.11g <ul style="list-style-type: none"> ◦ 17 dBm with 1 antenna • 802.11n (HT20) <ul style="list-style-type: none"> ◦ 20 dBm with 2 antennas • 802.11n (HT40) <ul style="list-style-type: none"> ◦ 20 dBm with 2 antennas 		5GHz <ul style="list-style-type: none"> • 802.11a <ul style="list-style-type: none"> ◦ 17 dBm with 1 antenna • 802.11n non-HT duplicate (802.11a duplicate) mode <ul style="list-style-type: none"> ◦ 17 dBm with 1 antenna • 802.11n (HT20) <ul style="list-style-type: none"> ◦ 20 dBm with 2 antennas • 802.11n (HT40) <ul style="list-style-type: none"> ◦ 20 dBm with 2 antennas 	
Note: The maximum power setting will vary by channel and according to individual country regulations. Refer to the product documentation for specific details.				
Available Transmit Power Settings	2.4GHz 20 dBm (100 mW) 17 dBm (50 mW) 14 dBm (25 mW) 11 dBm (12.5 mW) 8 dBm (6.25 mW) 5 dBm (3.13 mW) 2 dBm (1.56 mW) -1 dBm (0.78 mW)		5GHz 20 dBm (100 mW) 17 dBm (50 mW) 14 dBm (25 mW) 11 dBm (12.5 mW) 8 dBm (6.25 mW) 5 dBm (3.13 mW) 2 dBm (1.56 mW) -1 dBm (0.78 mW)	
Note: The maximum power setting will vary by channel and according to individual country regulations. Refer to the product documentation for specific details.				
Integrated Antenna	<ul style="list-style-type: none"> • 2.4 GHz, Gain 4.0 dBi, horizontal beamwidth 360° • 5 GHz, Gain 3 dBi, horizontal beamwidth 360° 			
Interfaces	<ul style="list-style-type: none"> • 10/100/1000BASE-T autosensing (RJ-45) • Management console port (RJ45) 			
Indicators	<ul style="list-style-type: none"> • Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors. 			
Dimensions (W x L x H)	<ul style="list-style-type: none"> • Access point (without mounting bracket): 8.7 x 8.7 x 1.84 in. (22.1 x 22.1 x 4.7 cm) 			
Weight	<ul style="list-style-type: none"> • 2.3 lbs (1.04 kg) 			
Environmental	<ul style="list-style-type: none"> • Nonoperating (storage) temperature: -22 to 185°F (-30 to 85°C) • Operating temperature: 32 to 104°F (0 to 40°C) • Operating humidity: 10 to 90% percent (non-condensing) 			
System Memory	<ul style="list-style-type: none"> • 128 MB DRAM • 32 MB flash 			
Input Power Requirements	<ul style="list-style-type: none"> • AP1140: 44 to 57 VDC • Power Supply and Power Injector: 100 to 240 VAC; 50 to 60 Hz 			
Powering Options	<ul style="list-style-type: none"> • 802.3af Ethernet Switch • Cisco AP1140 Power Injectors (AIR-PWRINJ4=) • Cisco AP1140 Local Power Supply (AIR-PWR-A=) 			
Power Draw	<ul style="list-style-type: none"> • AP1140: 12.95 W <p>Note: When deployed using PoE, the power drawn from the power sourcing equipment will be higher by some amount dependent on the length of the interconnecting cable. This additional power may be as high as 2.45W, bringing the total system power draw (access point + cabling) to 15.4W.</p>			
Warranty	Limited Lifetime Hardware Warranty			

Item	Specification
<p>Compliance</p>	<p>Standards</p> <ul style="list-style-type: none"> • Safety: <ul style="list-style-type: none"> ◦ UL 60950-1 ◦ CAN/CSA-C22.2 No. 60950-1 ◦ UL 2043 ◦ IEC 60950-1 ◦ EN 60950-1 • Radio approvals: <ul style="list-style-type: none"> ◦ FCC Part 15.247, 15.407 ◦ RSS-210 (Canada) ◦ EN 300.328, EN 301.893 (Europe) ◦ ARIB-STD 33 (Japan) ◦ ARIB-STD 66 (Japan) ◦ ARIB-STD T71 (Japan) ◦ AS/NZS 4268.2003 (Australia and New Zealand) ◦ EMI and susceptibility (Class B) ◦ FCC Part 15.107 and 15.109 ◦ ICES-003 (Canada) ◦ VCCI (Japan) ◦ EN 301.489-1 and -17 (Europe) ◦ EN 60601-1-2 EMC requirements for the Medical Directive 93/42/EEC • IEEE Standard: <ul style="list-style-type: none"> ◦ IEEE 802.11a/b/g, IEEE 802.11n, IEEE 802.11h, IEEE 802.11d • Security: <ul style="list-style-type: none"> ◦ 802.11i, Wi-Fi Protected Access 2 (WPA2), WPA ◦ 802.1X ◦ Advanced Encryption Standards (AES), Temporal Key Integrity Protocol (TKIP) • EAP Type(s): <ul style="list-style-type: none"> ◦ Extensible Authentication Protocol-Transport Layer Security (EAP-TLS) ◦ EAP-Tunneled TLS (TTLS) or Microsoft Challenge Handshake Authentication Protocol Version 2 (MSCHAPv2) ◦ Protected EAP (PEAP) v0 or EAP-MSCHAPv2 ◦ Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) ◦ PEAPv1 or EAP-Generic Token Card (GTC) ◦ EAP-Subscriber Identity Module (SIM) • Multimedia: <ul style="list-style-type: none"> ◦ Wi-Fi Multimedia (WMM™) • Other: <ul style="list-style-type: none"> ◦ FCC Bulletin OET-65C ◦ RSS-102
<p>Calculated Mean Time Between Failure (MTBF)</p>	<p>390,000 hours</p>

Service and Support

Cisco and Cisco Wireless LAN Specialized Partners offer a broad portfolio of end-to-end services based on proven methodologies for planning, designing, implementing, operating, and optimizing the performance of your wireless network. Cisco recommends the following services for the Cisco Aironet 1140 Series Access Points implementation:

Cisco Wireless LAN 802.11n Readiness Assessment Service

Prevent common challenges and reduce deployment costs by determining the readiness of your wired and wireless infrastructure.

Cisco Wireless LAN 802.11n Migration Service

Simplify the migration to high-performance, next generation 802.11n.

Cisco Wireless LAN Optimization Service

Evolve your 802.11n network to meet ever-changing network demands through planning and assessments, design, performance tuning, and ongoing support for system changes.

For more information about Cisco 802.11n planning and deployment services, visit

<http://www.cisco.com/go/wirelesslanservices>.

Limited Lifetime Hardware Warranty

This Cisco Aironet 1140 Series Access Point comes with a Limited Lifetime Warranty that provides full warranty coverage of the hardware for as long as the original end user continues to own or use the product. The warranty includes 10-day advance hardware replacement and ensures that software media is defect-free for 90 days. For more details, visit: <http://www.cisco.com/go/warranty>

For More Information

For more information about the Cisco Aironet 1140 Series, visit <http://www.cisco.com/go/wireless> or contact your local account representative.



Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV
Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, CCSI, Cisco Eos, Cisco Explorer, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco TrustSec, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1002R)