



FortiWiFi[®] Voice-80CS

Integrated Multi-Threat Security and IP PBX

Unified Business Gateway

The Fortinet FortiWiFi Voice-80CS is a multi-function security platform that protects voice and data communications for remote and branch offices. It combines the functionality of a multi-threat UTM security gateway, IP PBX, wireless LAN, VPN with strong encryption, router, and Ethernet switch into a single, integrated device. The FortiWiFi Voice-80CS platform meets the needs of small and medium sized organizations, as well as branch or remote offices. The single platform with its consolidated management console reduces the costs associated with configuring and managing your network security, VoIP security, IP PBX, and wireless LAN.

Embedded IP PBX Feature Set

The FortiWiFi Voice-80CS provides basic and advanced IP PBX functionality, as well as the widest range of threat management technologies available on the market. The IP PBX features include voicemail, message notification and unified messaging with interactive voice response (IVR). It provides support for SIP Trunking (Class 5 PSTN bypass) and supports standard SIP terminals, including hard- and softphones, WiFi phones, and SIP applications. In addition to SIP, the FortiWiFi Voice-80CS also supports integration with POTS and ISDN networks via analog telephone adapters (ATA). It also includes automatic call distribution (ACD), ad hoc conferencing and conference bridges, as well as configurable dial plans and direct inward dialing (DID). Its management features include system monitoring, statistics and logging data as well.

Comprehensive Threat Protection

The FortiWiFi Voice-80CS platform also provides comprehensive threat protection with Fortinet's FortiOS[™] enterprise-grade security and networking technologies. It integrates firewall, IPSec and SSL VPN, antivirus, antispam, intrusion prevention and web filtering into a single device at a single price. It includes data loss prevention (DLP), application control, and endpoint network access control (NAC) as well. In addition, Fortinet's Global Threat Research Team is on duty around the clock and around the world, looking for any changes in the threatscape. It delivers dynamic threat updates that protect your network against emerging threats.

Wireless Flexibility

The FortiWiFi Voice-80CS allows you to protect new and legacy wireless LAN environments with its 802.11 a/b/g/n support. It gives you the flexibility to deploy both wired and wireless devices while using a single platform to enforce all network security policies. The Express Card slot enables optional 3G wireless WAN connectivity, ensuring data connectivity in the event of a network failure.

DATASHEET



The FortiGate Product Family: Integrated Multi-Threat Protection

The FortiGate/FortiWiFi product family provides cost-effective, comprehensive protection against network, content, and application-level threats. It defends your environment from complex, sophisticated attacks without degrading network availability and affecting application performance.

FortiGate and FortiWiFi platforms combine the purpose-built FortiOS[™] security operating system with custom FortiASIC processors and other hardware to provide a comprehensive and high-performance array of security and networking functions.

The FortiGate/FortiWiFi product family delivers the highest level of network, content, and application security for enterprises of all sizes, while reducing total cost of ownership. With Fortinet, you deploy the network security you need to protect your intellectual property, preserve the privacy of critical customer information, and maintain regulatory compliance.

Features

Integrated data and VoIP security and IP PBX

Single device reduces costs

Benefits

Enables small and medium businesses, and ROBOs of larger organizations to deploy enterprise-grade voice and data security

Manages all security and IP PBX functionality from a single console, lowering costs and reducing deployment challenges


Industry Certification



| Technical Specifications | | FortiWiFi Voice-80CS |
|---|--|-------------------------|
| Hardware Specifications | | |
| 10/100/1000 WAN Interfaces (Copper, RJ-45) | | 2 |
| 10/100 Switch Interfaces (Copper, RJ-45) | | 6 |
| 10/100 DMZ Interfaces (Copper, RJ-45) | | 1 |
| Console (Copper, RJ-45) | | 1 |
| USB Interfaces | | 2 |
| Express Card Slot | | 1 |
| Wireless Standards Supported | | 802.11 a/b/g/n |
| System Performance | | |
| Firewall Throughput (1518 byte UDP packets) | | 1 Gbps |
| Firewall Throughput (512 byte UDP packets) | | 500 Mbps |
| IPSec VPN Throughput | | 100 Mbps |
| IPS Throughput* | | 200 Mbps |
| Antivirus Throughput* | | 65 Mbps |
| Gateway-to-Gateway IPSec VPN Tunnels (System / VDOM) | | 500 / 50 |
| Client-to-Gateway IPSec VPN Tunnels | | 1,500 |
| Concurrent Sessions | | 400,000 |
| New Sessions/Sec | | 10,000 |
| Concurrent SSL VPN Users (Recommended Max) | | 100 |
| Virtual Domains (Max / Default) | | 10 / 10 |
| Maximum Number of Policies (System / VDOM) | | 5,000 / 500 |
| Unlimited User Licenses | | Yes |
| Dimensions | | |
| Height x Width x Length (in) | | 1.75 x 10.87 x 6.13 in. |
| Height x Width x Length (cm) | | 4.45 x 27.61 x 15.57 cm |
| Weight | | 3.5 lbs (1.59 kg) |
| Rack Mountable | | No |
| Antivirus performance is measured based on HTTP traffic with 32 Kbyte file attachments and IPS performance is measured based on UDP traffic with 512 byte packet size. Actual performance may vary depending on network traffic and environments. | | |

| Technical Specifications | | FortiWiFi Voice-80CS |
|--|--|--|
| Environment | | |
| Power Required | | 100-240 VAC, 50-60 Hz 2 Amp max |
| Power Consumption (AVG) | | 39W |
| Operating Temperature | | 32 – 104 deg F (0 – 40 deg C) |
| Storage Temperature | | -13 to 158 deg F (-25 to 70 deg C) |
| Humidity | | 5 to 95% non-condensing |
| Compliance | | |
| | | FCC Class B, UL/CUL/VCCI/C-tick, CE |
| Certifications | | |
| | | ICSA Labs: Firewall, AV, IPSec VPN, SSL VPN, IPS |
| PBX Specifications | | |
| Maximum Number of Registered SIP User Agents | | 50 |
| Number of SIP Clients Registering per Second | | 50 |
| Maximum Number of Concurrent Calls | | 20 |
| Maximum Number of Call Attempts per Second | | 5 |
| Conference Lines | | 5 |
| Voice Mail Storage | | Approximately 60 hours |
| VoIP Protocol | | SIP v2 (RFC3261), RTCP |
| Voice Codec | | G.711.a/u |
| PBX Features | | Voicemail, Unified Messaging, Auto Attendant, Automatic Call Distribution, Direct Inward Dialing, Conference Bridges, Statistics and Logging |
| IP Telephony Features | | Echo cancellation G.168 |

FortiWiFi Voice-80CS Voice Network



Voice Network Consolidation

The FortiWiFi Voice-80CS platform allows you to consolidate all of your voice traffic into a single platform. Integrating VoIP and POTS into a single point of control enables you to reduce your telephony costs by consolidating multiple products.

The FortiWiFi Voice-80CS gives you the flexibility you need to connect your small offices / branch offices with traditional Telcos, VoIP service providers, as well as the corporate voice and data network.

FortiGuard® Security Subscription Services deliver dynamic, automated updates for Fortinet products including antivirus, intrusion prevention, web filtering, antispam, vulnerability and compliance management, application control, web application firewall, and database security services.

FortiCare™ Support Services provide global support for all Fortinet products and services. Support plans start with 8x5 Enhanced Support with “return and replace” hardware replacement or 24x7 Comprehensive Support with advanced replacement. All hardware products include a 1-year limited hardware warranty and 90-day limited software warranty.

FORTINET®

GLOBAL HEADQUARTERS

Fortinet Incorporated
1090 Kifer Road, Sunnyvale, CA 94086 USA
Tel +1.408.235.7700
Fax +1.408.235.7737
www.fortinet.com/sales

EMEA SALES OFFICE – FRANCE

Fortinet Incorporated
120 rue Albert Caquot
06560, Sophia Antipolis, France
Tel +33.4.8987.0510
Fax +33.4.8987.0501

APAC SALES OFFICE – SINGAPORE

Fortinet Incorporated
61 Robinson Road, #09-04 Robinson Centre
Singapore 068893
Tel +65-6513-3730
Fax +65-6223-6784

Copyright© 2010 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, and FortiGuard®, are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance metrics contained herein were attained in internal lab tests under ideal conditions. Network variables, different network environments and other conditions may affect performance results, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding contract with a purchaser that expressly warrants that the identified product will perform according to the performance metrics herein. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any guarantees. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable. Certain Fortinet products are licensed under U.S. Patent No. 5,623,600.